



Product Features

- inlet male pipe thread
- with socket wrench bonnet
- with aerator for automatic drainage
- can be extended to any length at construction site
- incl. hose coupling for common connection systems
- free from dead spots
- wetted metal parts made of dezincification-free and corrosion-resistant gunmetal (in closed position), resistant against aggressive water
- flexible installation length with sliding wall disc in outdoor area
- suitable for fast subsequent installation on already finished outer wall
- pre-assembled
- high discharge capacity of 40 l / min (1 bar)
- EPDM-seat gasket
- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water

Standards and Approvals

- WRAS approval

Technical Data

- min. installation depth 150 mm
- max. installation depth 492 mm
- pressure rating PN 16
- max. operating temperature 90 °C

Part No.	DN	A1	A2	D1 (mm)	D2 (mm)	H1 (mm)	H2 (mm)	H3 (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	L5 (mm)	L6 (mm)	T1 (mm)	flow at 0.05 Mpa (l/s)	flow at 0.1 MPa (l/s)	flow at 0.15 Mpa (l/s)
5771101500	15	R 1/2	G 3/4	26.4	15	72	120	100	617	238	124.5	61.5	492.5	255	70	0.4	0.67	0.8

Accessories

operating handle for FROSTI®, lockable, figure 575 00 003
 dismantling key for lockable operating handle, figure 575 01 003